





# JERRIMO

# JERRIMO




Proiettore LED a plafone e sospensione  
Ceiling-mounted and pendant LED spotlight

Corpo in estruso di alluminio verniciato con polveri epossidiche previa fosfatazione.  
Dissipatore in pressofusione di alluminio con ventilazione forzata per versione 3.000 lm.  
Ottica in alluminio anodizzato lucido MD fascio medio - LA fascio largo.  
Sorgente luminosa LED.  
Emissione diretta.  
Installazione a plafone o sospensione.  
**A richiesta**  
- Temperatura di colore del LED K diversa da quella specificata.  
- CRI > 90.  
- Kit di sospensione.

Extruded aluminium body coated with epoxy powders after phosphating.  
Die-cast aluminium heat sink with forced ventilation for 2000 a 3000 lm version.  
42° - 67° polished anodised aluminium optic.  
LED light source. Direct light emission.  
Ceiling-mounted or pendant installation.  
**On request**  
- LED color temperature K different from specified one.  
- CRI > 90.  
- Pendant mounting kit.

## JERRIMO

IEE = A+



Lumen*	Watt**	Ta***	fascio beam	K Kelvin	durata ore hours duration	codice code	alimentazione power supply	colore color
2.000 lm	22 W	+5° +40°	LA fascio largo wide beam	3.000 K	50.000	JRM2000WLA	— CAE elettronica electronic	01 bianco white 02 nero black 05 grigio silver
				4.000 K	50.000	JRM2000NLA		
			MD fascio medio medium beam	3.000 K	50.000	JRM2000WMD		
				4.000 K	50.000	JRM2000NMD		
3.000 lm	32 W	+5° +40°	LA fascio largo wide beam	3.000 K	50.000	JRM3000WLA		
				4.000 K	50.000	JRM3000NLA		
			MD fascio medio medium beam	3.000 K	50.000	JRM3000WMD		
				4.000 K	50.000	JRM3000NMD		

accessori accessories

codice code

colore color

Kit sospensione per Jerrimo. Ceiling-mounting kit for Jerrimo.

JRM-SOS

01, 02, 05

