



Luminarias / Luminaires



Micro downlights



DOWNLIGHTS FIJOS

FIXED DOWNLIGHTS

Empotrables / Recessed

| | Flujo luz Light output | Temperatura color disponible °K Available color temperature °K | CRI Disponibles Available CRI |
|---------------|---------------------------|---|----------------------------------|
| MRD 7 | 450 lm | 2.700 /4.000°K | CRI> 80 |
| MRD 10 | 600 lm | 2.700 /4.000°K | CRI> 80 |

Con driver electrónico.
Sistema de disipación pasiva.
Óptica 24º y cristal transparente.
Opción regulable.

*With electronic control driver.
Passive heatsink built-in.
24º Round Louvre and transparent glass.
Available dimmable driver as an option.*

Consultar tabla de potencias/consumos actualizados en www.castanweb.com/watts.html
See actual power consumptions on www.castanweb.com/watts.html

COMPOSICIÓN DE REFERENCIAS / REFENCE PLANNING

.27 2700°K CRI>80 **.ER** Regulable/
.40 4000°K CRI>80 *Dimmable*

EJEMPLO DE REFERENCIA / REFERENCE EXAMPLE:

MRD 7.27: 450 Lm 2.700°K Blanco / White

ACABADOS / FINISHES



DIRECCION LUZ / LIGHT DIRECTION



TECNOLOGÍA / TECHNOLOGY

