



Luminarias orientables / Adjustable luminaires



# Micro downlights



## DOWNLIGHTS BASCULANTES

### TILTED DOWNLIGHTS

#### Empotrables / Recessed

	Flujo luz Light output	Temperatura color disponible °K Available color temperature °K	CRI Disponibles Available CRI
<b>MRD 7 OS</b>	450 lm	2.700/4.000°K	CRI> 80
<b>MRD 10 OS</b>	600 lm	2.700/4.000°K	CRI> 80

Con driver electrónico.  
Sistema de disipación pasiva.  
Óptica 24º y cristal transparente.  
Opción regulable.

*With electronic control driver.  
Passive heatsink built-in.  
24º round Louvre and transparent glass.  
Available dimmable driver as an option.*

Consultar tabla de potencias/consumos actualizados en [www.castanweb.com/watts.html](http://www.castanweb.com/watts.html)  
See actual power consumptions on [www.castanweb.com/watts.html](http://www.castanweb.com/watts.html)

#### COMPOSICIÓN DE REFERENCIAS / REFERENCE PLANNING

**.27** 2700°K CRI>80    **.ER** Regulable/  
**.40** 4000°K CRI>80    *Dimmable*

#### EJEMPLO DE REFERENCIA / REFERENCE EXAMPLE:

**MRD 7.27 OS:** 450 Lm 2.700°K Blanco / White

#### ACABADOS / FINISHES



#### DIRECCION LUZ / LIGHT DIRECTION



#### TECNOLOGÍA / TECHNOLOGY

