



Sistema / System



## Minus Line LED



## SISTEMA LINEAL DE EMPOTRAR

## RECESSED LINEAR SYSTEM

## Módulos de alta potencia / High power modules

|                | Consumo<br>Consumption | Flujo luz<br>Light output | Temperatura color disponible °K<br>Available color temperature °K | CRI Disponibles<br>Available CRI | L - Longitud<br>L - Length |
|----------------|------------------------|---------------------------|---|----------------------------------|----------------------------|
| <b>MLI 30</b>  | 3.500 lm               | 30W                       | 3.000/4.000°K   | CRI> 80                          | 847 mm                     |
| <b>MLI 43</b>  | 4.700 lm               | 43W                       | 3.000/4.000°K   | CRI> 80                          | 1.127 mm                   |
| <b>MLI 53</b>  | 5.950 lm               | 53W                       | 3.000/4.000°K   | CRI> 80                          | 1.408 mm                   |
| <b>MLI 63</b>  | 7.150 lm               | 63W                       | 3.000/4.000°K   | CRI> 80                          | 1.688 mm                   |
| <b>MLI 75</b>  | 8.300 lm               | 75W                       | 3.000/4.000°K   | CRI> 80                          | 1.969 mm                   |
| <b>MLI 85</b>  | 9.500 lm               | 86W                       | 3.000/4.000°K   | CRI> 80                          | 2.249 mm                   |
| <b>MLI 95</b>  | 10.700 lm              | 96W                       | 3.000/4.000°K   | CRI> 80                          | 2.530 mm                   |
| <b>MLI 110</b> | 11.900 lm              | 106W                      | 3.000/4.000°K   | CRI> 80                          | 2.811 mm                   |
| <b>MLI 121</b> | 13.100 lm              | 116W                      | 3.000/4.000°K   | CRI> 80                          | 3.091 mm                   |

Con equipo electrónico incorporado.  
Opción equipo electrónico regulable (DALI, Touch&Dimm).  
Difusor opal.

*With electronic control gear built-in  
Electronic dimmable control gear (Dali, Touch&Dimm) available as an option.  
Opal diffuser.*

## COMPOSICIÓN DE REFERENCIAS / REFERENCE PLANNING

**.30** 3.000°K CRI>80  
**.40** 4.000°K CRI>80

**.ER** electrónico regulable  
dimmable

## EJEMPLO DE REFERENCIA / REFERENCE EXAMPLE:

**MLI 85.40 N:** 86W 9500lm 4000° 2.249 mm  
Negro / Black

ACCESORIOS ver pág. 126 y 128  
ACCESSORIES see page 126 and 128

ACABADOS / FINISHES

DIRECCION LUZ /  
LIGHT DIRECTIONTECNOLOGÍA/  
TECHNOLOGY