



Sistema / System



Minus LED



SISTEMA LINEAL DE PARED LED

WALL LINEAR LED SYSTEM

Módulos de alta potencia / High power modules

	Flujo luz Light output	Consumo Consumption	Temperatura color disponible °K Available color temperature °K	CRI Disponibles Available CRI	L - Longitud L - Length
AMI 30	3.500 lm	30W	3.000/4.000°K	CRI> 80	847 mm
AMI 43	4.700 lm	43W	3.000/4.000°K	CRI> 80	1.127 mm
AMI 53	5.950 lm	53W	3.000/4.000°K	CRI> 80	1.408 mm
AMI 63	7.150 lm	63W	3.000/4.000°K	CRI> 80	1.688 mm
AMI 75	8.300 lm	75W	3.000/4.000°K	CRI> 80	1.969 mm
AMI 85	9.500 lm	86W	3.000/4.000°K	CRI> 80	2.249 mm
AMI 95	10.700 lm	96W	3.000/4.000°K	CRI> 80	2.530 mm
AMI 110	11.900 lm	106W	3.000/4.000°K	CRI> 80	2.811 mm
AMI 121	13.100 lm	116W	3.000/4.000°K	CRI> 80	3.091 mm

Con equipo electrónico incorporado.
Opción equipo electrónico regulable (DALI, Touch&Dimm).
Difusor opal.

*With electronic control gear built-in
Electronic dimmable control gear (Dali, Touch&Dimm) available as an option.
Opal diffuser.*

COMPOSICIÓN DE REFERENCIAS / REFERENCE PLANNING

.30	3.000°K	CRI>80	.ER electrónico regulable DALI dimmable DALI
.40	4.000°K	CRI>80	

EJEMPLO DE REFERENCIA / REFERENCE EXAMPLE:

AMI 85.40 N: 86W 9.500 lm 4000° K 2.249 mm Negro / Black

ACCESORIOS ver pág. 126 y 128
ACCESSORIES see page 126 and 128

ACABADOS / FINISHES



DIRECCION LUZ / LIGHT DIRECTION



TECNOLOGÍA / TECHNOLOGY

