




Step



ACCESORIOS / ACCESSORIES



STP-CEH Caja de empotrar en hormigón /
Concrete box

COMPOSICIÓN DE REFERENCIAS / REFERENCE PLANNING

.30	3.000°K	CRI>80	.12 óptica/lens 12°	·DRV 10W 230V IP65 driver incluido/ included ·CEM Cristal mate Matt glass
.40	4.000°K	CRI>80	.25 óptica/lens 25°	
			.40 óptica/lens 40°	

EJEMPLO DE REFERENCIA / REFERENCE EXAMPLE:

STP 5.30.12 AC: 5W 430 LM 3.000°K 12° Acero brillo / Polished stainless steel
STP 5.40. CEM: 5W 430 LM 4.000°K 180° Cristal mate / matt glass

PROYECTORES EMPOTRABLES DE EXTERIOR LED IP 67

RECESSED OUTDOOR LED SPOTLIGHTS IP 67

Empotrables en suelo y pared / Wall & floor lights

	Flujo luz Light output	Consumo Consumption	Temperatura color disponible °K Available color temperature °K	CRI Disponibles Available CRI
STP 5	430 lm	5W	3.000/4.000°K	CRI> 80

Fabricado en acero inoxidable A4 y aluminio anodizado.
 Ópticas disponibles 12°, 25° y 40°, con cristal anticondensación transparente.
 Con driver electrónico 350 mA remoto.
 Opción cristal mate para 180°.
 Consultar configuración de driver.
 Opción driver incorporado .DRV.

Made with inox steel A4 and anodized aluminium
 Available optics 12°, 25° and 40°, with not condensation transparent glass.
 With electronic 350 mA driver installed as remote.
 Optional not condensation matt glass for 180°.
 Ask for driver connection and configuration.
 Optional driver built-in .DRV.

ACABADOS / FINISHES



DIRECCION LUZ / LIGHT DIRECTION



TECNOLOGÍA / TECHNOLOGY

